

SAFETY DATA SHEET SUPER RESIN POLISH

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name SUPER RESIN POLISH

Product number SRP001, SRP500, SRP325, SRP100, SRP100N, SRP100SW/F, SRP325NL/F,

SRP325SW/F, SRP325JAP, SRPSACHET, SRP325SCAN, SRP001SCAN, SRP500SCAN, SRP100JAP, SRP325VW, SRP500CA, SRPSACHETCA, SRP001SW/F, SRP100NL/F,

SRP500AU, SRP001AU, SRP100AU, SRP325AU

Internal identification SRP/RC/1/23415

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Polish for use on motor vehicle bodies

1.3. Details of the supplier of the safety data sheet

Supplier Autoglym

Works Road Letchworth Herts SG6 1LU UK

sds@autoglym.com

1.4. Emergency telephone number

Emergency telephone +44 (0) 1462 489498 (24Hrs)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards STOT SE 3 - H336

Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements H336 May cause drowsiness or dizziness.

EUH208 Contains 2-methyl-2H-isothiazol-3-one, 1,2-benzisothiazol-3(2H)-one. May produce

an allergic reaction.

SUPER RESIN POLISH

Precautionary statements P312 Call a POISON CENTER/ doctor if you feel unwell.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/ container in accordance with national regulations.

P261 Avoid breathing vapours. P102 Keep out of reach of children.

P271 Use only outdoors or in a well-ventilated area.

Contains Naptha (Petroleum), Hydrotreated Heavy

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Naptha (Petroleum), Hydrotreated Heavy

10-30%

CAS number: 64742-48-9 EC number: 265-150-3 REACH registration number: 01-

2119486659-16-XXXX

Classification

Classification (67/548/EEC or 1999/45/EC)
Carc. Cat. 2;R45 Muta. Cat. 2;R46 Xn;R65

Flam. Liq. 3 - H226

STOT SE 3 - H336

Asp. Tox. 1 - H304

Distillates (petroleum), hydrotreated light

5-10%

CAS number: 64742-47-8 EC number: 265-149-8 REACH registration number: 01-

2119484819-18-XXXX

Classification

Asp. Tox. 1 - H304

2-methyl-2H-isothiazol-3-one

<1%

CAS number: 2682-20-4 EC number: 220-239-6

M factor (Acute) = 1

Classification

Acute Tox. 3 - H301

Acute Tox. 3 - H311

Skin Corr. 1B - H314

Eye Dam. 1 - H318 Skin Sens. 1 - H317

STOT SE 3 - H335

Aquatic Acute 1 - H400

SUPER RESIN POLISH

Bronopol <1%

CAS number: 52-51-7 EC number: 200-143-0 REACH registration number: 01-

2119980938-15-XXXX

M factor (Acute) = 10

Classification

Acute Tox. 4 - H302 Acute Tox. 4 - H312 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335 Aquatic Acute 1 - H400

1,2-benzisothiazol-3(2H)-one <1%

M factor (Acute) = 10

Classification

Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Acute 1 - H400

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Remove person to fresh air and keep comfortable for breathing.

Ingestion Do not induce vomiting. Get medical attention immediately.

Skin contact Rinse immediately with plenty of water. Take off contaminated clothing and wash it before

reuse. Get medical attention if any discomfort continues.

Eye contact Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get

medical attention. Remove any contact lenses and open eyelids wide apart. Rinse with water.

Get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation Vapours may cause drowsiness and dizziness.

Ingestion May cause stomach pain or vomiting.

Skin contact May cause skin sensitisation or allergic reactions in sensitive individuals.

Eye contact May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

SECTION 5: Firefighting measures

5.1. Extinguishing media

SUPER RESIN POLISH

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion

Oxides of carbon.

products

for firefighters

5.3. Advice for firefighters

Special protective equipment

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Follow precautions for safe handling described in this safety data sheet. Take precautionary

measures against static discharges. Provide adequate ventilation.

6.2. Environmental precautions

Environmental precautions Spillages or uncontrolled discharges into watercourses must be reported immediately to the

Environmental Agency or other appropriate regulatory body. Avoid discharge into drains or

watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Absorb spillage with inert, damp, non-combustible material. Flush contaminated area with

plenty of water. Collect and place in suitable waste disposal containers and seal securely.

Dispose of contents/container in accordance with local regulations.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid contact with skin and eyes.

Advice on general

When using do not eat, drink or smoke. Wash hands thoroughly after handling.

occupational hygiene

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in

the original container.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Protective equipment





Appropriate engineering controls

Provide adequate ventilation.

SUPER RESIN POLISH

Eye/face protection Wear eye protection. EN 166:2001

Hand protection Wear protective gloves made of the following material: Nitrile rubber. The breakthrough time

for any glove material may be different for different glove manufacturers.

Hygiene measures Wash at the end of each work shift and before eating, smoking and using the toilet.

Respiratory protection Respiratory protection not required.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Creamy liquid.

Colour White.

Odour Characteristic.

Odour threshold No information available.

pH (concentrated solution): 5.5

Melting point No information available.

Flash point 61°C Setaflash closed cup.

Evaporation rate No information available.

Evaporation factor No information available.

Upper/lower flammability or

explosive limits

No information available.

Vapour pressure

No information available.

Vapour density

No information available.

Relative density ~ 0.98

Bulk density

No information available.

Partition coefficient

No information available.

Auto-ignition temperature

No information available.

Decomposition Temperature

No information available.

Viscosity Sinematic viscosity > 20.5 mm²/s.

Explosive properties No information available.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

No potentially hazardous reactions known.

reactions

10.4. Conditions to avoid

SUPER RESIN POLISH

Conditions to avoid No specific requirements are anticipated under normal conditions of use.

10.5. Incompatible materials

Materials to avoid Avoid contact with the following materials: Strong acids. Strong alkalis.

10.6. Hazardous decomposition products

Hazardous decomposition

Not known.

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 100,000.0

Acute toxicity - dermal

ATE dermal (mg/kg) 300,000.0

Skin sensitisation

Skin sensitisation May cause sensitisation or allergic reactions in sensitive individuals.

General information This product has low toxicity.

Inhalation Vapours may cause drowsiness and dizziness.

SECTION 12: Ecological Information

Ecotoxicity The product is not expected to be hazardous to the environment.

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

Bioaccumulative potential Not determined.

Partition coefficient No information available.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations

Disposal methodsDispose of contents/container in accordance with local regulations.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

SUPER RESIN POLISH

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18

December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

SECTION 16: Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 23/04/2015

Revision 11

SDS number 21679

Hazard statements in full H226 Flammable liquid and vapour.

H301 Toxic if swallowed. H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin. H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

EUH208 Contains 2-methyl-2H-isothiazol-3-one, 1,2-benzisothiazol-3(2H)-one. May produce

an allergic reaction.

SUPER RESIN POLISH

Signature Daniel Higgs

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.